



# Elements LED In-Wall: Wind

## MODEL # 10676

Envisioned as a wayfinding marker or illuminated art piece, these 3' or 4' tall linear lighting fixtures are recessed into the wall. On the surface of the wall, only a minimal frame is visible, but inside the wall light flows forth. The steel outer frame comes primed for painting to match any interior. At the back of the channel is a smooth brass plate, and around the sides of the channel is a strip of LEDs which radiates bright, warm, ambient light. Dim for romance, brighten for impact. Designed by Doyle Crosby.

## MATERIALS

Aluminum, Steel

## FINISHES

White Primer, Antiqued Boyd Brass, Gossamer Gold, Satin Brass or Satin Nickel

## LAMPING

36" nominal: 36.625" (930 mm) LED at 40w, 2700 K, 90+ CRI. Fixture can be dimmed using 0-10v low-voltage 4-wire dimming controls and wiring. Other systems to be quoted.

48" nominal: 48.625" (1235 mm) LED at 56w, 2700 K, 90+ CRI. Fixture can be dimmed using 0-10v low-voltage 4-wire dimming controls and wiring. Other systems to be quoted.

3500°k, color temperatures are available.

## DIMENSIONS

36" nominal:

H 36.625" x W 5.625" x D .125"

H 930 mm x W 143 mm x D 3 mm

## WEIGHT

16 lbs.

7.3 kg

48" nominal:

H 48.625" x W 5.625" x D .125"

H 1235 mm x W 143 mm x D 3 mm

21 lbs.

9.5 kg

## NOTES

- Backbox: H 36" x W 5" x D 3.25" (H 914 mm x W 127 mm x D 83 mm) OR H 48" x W 5" x D 3.25" (H 1219 mm x W 127 mm x D 83 mm)
- Center of outlet box to top of fixture: 18.25" (464 mm) OR 24.25" (616 mm)
- Reflector: brass plate
- Outer frame: available in White Primer for painting by others (standard)
- Optional cover lens: Clear Acrylic (upcharge)
- Horizontal or vertical mounting
- This fixture requires recessed mounting. See full installation instructions for mounting details
- ADA compliant at any mounting height
- UL listed (or equivalent) for damp locations

