



# Emanation Mirrored In-Wall

## MODEL # 46001, 46002

The Emanation LED Mirrored In-Wall provides punctuations of visible light on any custom mirror. To illuminate ones' face, filtered, non-glare light glows through a three-inch-wide mirrored faceplate on which there is an etched pattern. It is recessed mounted to be flush with the surrounding mirror for uninterrupted reflection. Designed by Tony Garrett

## MATERIALS

Mirrored

## FINISHES

Soda lime green glass OR Starfire low-iron glass, mirror patterns: Diamond, Dots, Open Etched Rectangle, Slots or Zig-zag

## LAMPING

46001: LED at 31w, 3000 K (standard) 90+ CRI providing about 1600 fixture lumens. Universal voltage 120v-277v. LED lamps standard in this fixture can be dimmed using 0-10v low-voltage dimming controls and wiring. Other systems to be quoted. 2700°k color temperature, and Dim to Warm LEDs are available.

46002: LED at 38w, 3000 K (standard), 90+ CRI providing about 2000 fixture lumens. Universal voltage 120v-277v. The LED lamps standard in this fixture can be dimmed using 0-10v low-voltage dimming controls and wiring. Other systems to be quoted. 2700°k color temperature, and Dim to Warm LEDs are available.

## NOTES

- Backplate  
46001: H 41.25" x W 3.25" x D 3.25"  
(H 1048 mm x W 82.5 mm x D 82.5 mm) 46002:  
H 53" x W 3.25" x D 3.25"  
(H 1346 mm x W 82.5 mm x D 82.5 mm)
- Center of outlet box to top of fixture:  
46001: 20.625" (524 mm)  
46002: 26.5" (673 mm)
- ADA compliant at any mounting height
- UL listed (or equivalent) for damp locations
- CE Approved version available upon special request (no upcharge)
- Diffuser: 0.25" soda lime green glass mirror (standard) or Starphire glass mirror (upcharge)
- Backplate: matte black
- Can be either recessed or surface mounted
- Surface mount: must mount to a mud-ring or switch box
- Recessed mount: see full installation instructions for mounting details
- Photometric report and ies file available for download at [www.boydlighting.com](http://www.boydlighting.com)

