



Emanation Mirrored In-Wall

MODEL # 46000, 46001, 46002

The Emanation LED Mirrored In-Wall provides punctuations of visible light on any custom mirror. To illuminate ones' face, filtered, non-glare light glows through a three-inch-wide mirrored faceplate on which there is an etched pattern. It is recessed mounted to be flush with the surrounding mirror for uninterrupted reflection. Designed by Doyle Crosby.

MATERIALS

Mirrored

FINISHES

Soda lime green glass OR Starphire low-iron glass, mirror patterns: Diamond, Dots, Open Etched Rectangle, Slots or Zig-zag

LAMPING

46000: LED at 20w, 3000 K (standard) 90+ CRI providing about 1050 fixture lumens. Universal voltage 120v-277v. The LED lamps standard in this fixture can be dimmed using 0-10v low-voltage dimming controls and wiring. Other systems to be quoted. 2700°k color temperature, and Dim to Warm LEDs are available.

46001: LED at 31w, 3000 K (standard) 90+ CRI providing about 1600 fixture lumens. Universal voltage 120v-277v. LED lamps standard in this fixture can be dimmed using 0-10v low-voltage dimming controls and wiring. Other systems to be quoted. 2700°k color temperature, and Dim to Warm LEDs are available.

46002: LED at 38w, 3000 K (standard), 90+ CRI providing about 2000 fixture lumens. Universal voltage 120v-277v. The LED lamps standard in this fixture can be dimmed using 0-10v low-voltage dimming controls and wiring. Other systems to be quoted. 2700°k color temperature, and Dim to Warm LEDs are available.

NOTES

- Backplate
46000: H 29.5" x W 3.25" x D 3.25"
(H 749 mm x W 82.5 mm x D 82.5 mm)
46001: H 41.25" x W 3.25" x D 3.25"
(H 1048 mm x W 82.5 mm x D 82.5 mm)
46002: H 53" x W 3.25" x D 3.25"
(H 1346 mm x W 82.5 mm x D 82.5 mm)
- Center of outlet box to top of fixture:
46000: 14.75" (375 mm)
46001: 20.625" (524 mm)
46002: 26.5" (673 mm)
- ADA compliant at any mounting height
- UL listed (or equivalent) for damp locations
- CE Approved version available upon special request (no upcharge)
- Diffuser: 0.25" soda lime green glass mirror (standard) or Starphire glass mirror (upcharge)
- Backplate: matte black
- Can be either recessed or surface mounted
- Surface mount: must mount to a mud-ring or switch box
- Recessed mount: see full installation instructions for mounting details
- Photometric report and ies file available for download at www.boydlighting.com

