



Iwall LED Sconce

MODEL #10139, 10140

Iwall has a glass fluted diffuser. It is mounted on the wall with rectangular backplates or no backplates on mirror mounting for 'floating' mirror effect. Designed by Doyle Crosby.

MATERIALS

Brass and glass

FINISHES

Polished Nickel or Satin Nickel

LAMPING

Iwall 3' (10139):

LED, 14 Watts, 3000k, 90 CRI, 120-277 Volts

Dimmable with ELV and Triac dimmers. Driver to be remotely installed. 2700k LEDs available.

Iwall 4' (10140):

LED, 18 Watts, 3000k, 90 CRI, 120-277 Volts

Dimmable with ELV and Triac dimmers. Driver to be remotely installed. 2700k LEDs available.

DIMENSIONS	WEIGHT
Iwall 3' (10139):	
W 2.0" x H 38.50" x D 3.75"	9 lbs.
(51 mm x 978 mm x 95 mm)	4.1 kg
Iwall 4' (10140):	
W 2.0" x H 50.5" x D 3.75"	10 lbs
(51 mm x 1280 mm x 95 mm)	4.5 kg

NOTES

- Optional Iwall Backplates:
3.62" W x 4.5" x .25 (92 x 114 x 6 mm)
- Center of outlet box to top of fixture:
1.5" (38mm). 2.25" (57mm) with optional backplates.
- ADA compliant at any mounting height
- UL listed (or equivalent) for damp locations
- Diffuser: clear, fluted glass
- Partially obscured 0.25" polished nickel wire way
- Horizontal or vertical mounting.
- Must mount to a mud-ring or switch-box
- Optional: mirror mount modification available (no backplates)
- Patent Design: D550,885.

