



# Emanation Mirrored In-Wall

## MODEL # 46000, 46001, 46002

The Emanation LED Mirrored In-Wall provides punctuations of visible light on any custom mirror. To illuminate ones' face, filtered, non-glare light glows through a three-inch-wide mirrored faceplate on which there is an etched pattern. It is recessed mounted to be flush with the surrounding mirror for uninterrupted reflection. Designed by Doyle Crosby.

## MATERIALS

Mirrored

## FINISHES

Soda lime green glass OR Starphire low-iron glass, mirror patterns: Diamond, Dots, Open Etched Rectangle, Slots or Zig-zag

## LAMPING

46000: LED at 20w, 3000 K (standard) OR 2700 K, OR 3500 K, 90+ CRI providing about 1050 fixture lumens. Universal voltage 120v-277v. The LED lamps standard in this fixture can be dimmed using 0-10v low-voltage dimming controls and wiring. Other systems to be quoted. Dim to Warm LEDs available with an upcharge.

46001: LED at 31w, 3000 K (standard) OR 2700 K, OR 3500 K, 90+ CRI providing about 1600 fixture lumens. Universal voltage 120v-277v. The LED lamps standard in this fixture can be dimmed using 0-10v low-voltage dimming controls and wiring. Other systems to be quoted. Dim to Warm LEDs available with an upcharge.

46002: LED at 38w, 3000 K (standard) OR 2700 K, OR 3500 K, 90+ CRI providing about 2000 fixture lumens. Universal voltage 120v-277v. The LED lamps standard in this fixture can be dimmed using 0-10v low-voltage dimming controls and wiring. Other systems to be quoted. Dim to Warm LEDs available with an upcharge.

## NOTES

- Backplate  
46000: H 28.75" x W 2.75" x D 3"  
(H 730 mm x W 70 mm x D 76 mm)  
46001: H 40.5" x W 2.75" x D 3"  
(H 1029 mm x W 70 mm x D 76 mm)  
46002: H 52.25" x W 2.75" x D 3"  
(H 1327mm x W 70 mm x D 76 mm)
- Center of outlet box to top of fixture:  
46000: 14.75" (375 mm)  
46001: 20.625" (524 mm)  
46002: 26.5" (673 mm)
- ADA compliant at any mounting height
- UL listed (or equivalent) for damp locations
- CE Approved version available upon special request (no upcharge)
- Diffuser: 0.25" soda lime green glass mirror (standard) or Starphire glass mirror (upcharge)
- Backplate: matte black
- Can be either recessed or surface mounted
- Surface mount: must mount to a mud-ring or switch box
- Recessed mount: see full installation instructions for mounting details
- Photometric report and ies file available for download at [www.boydlighting.com](http://www.boydlighting.com)

